



700 Series

Fryers 700

### GAS FRYER, FG7-10

1120830500

#### DIMENSIONS

		Article	Packed
Length	mm	<b>700,00</b>	<b>742,00</b>
Depth	mm	<b>775,00</b>	<b>835,00</b>
Height	mm	<b>850,00</b>	<b>1.060,00</b>
Weight	Kg	<b>104,00</b>	<b>119,00</b>
Volume	m3	<b>0,46</b>	<b>0,66</b>

GAS FRYER, FG7-10

Made of stainless steel

Capacity: two 15 litre oil/well.

Tank equipment: 1 basket 250x280 or 2 small baskets 250x135 mm .

Cast iron burners.

Thermostats temperature control 60 °C to 195 °C.

Automatic burner ignition by means of an electromagnetic valve, with pilot light and thermocouple.

Safety thermostat.

Drainage taps.

Power: 26000 Kcal/h. (30.22 kW).

Electrical connection 230 V - 1+N+T.

Dimensions: 700 x 775 x 850 mm.

#### ELECTRICITY

Electric power		KW	0,05
230V -1+N			<b>2x1,5+T - 2 A</b>
230V - III			
400V - III+N			

#### PLUMBING - WATER

#### GAS

Power		KW	<b>30,22</b>
		Kcal/h	<b>25.989,20</b>
LPG	Consumption (kg/h)		<b>2,50</b>
	Pressure (g/cm2)		<b>37,00</b>
Natural gas	Consumption (m3/h)		<b>3,18</b>
	Pressure (g/cm2)		<b>18,00</b>

#### VAPOR

Not used

#### AIRE Comprimido

Not used

#### Certification EQNET- CE

99AR284

Connections	X	Y	Z	Diameter	Information
ELECTRICITY	286	540	150		Prever Interruptor diferencial
ELECTRICITY	636	540	150		Prever Interruptor diferencial
GAS	662	492	105	R.3/4"G	Prever regulador y llave de corte individual
GAS	312	492	105	R.3/4"G	Prever regulador y llave de corte individual

