



## Standard and Wide Entry Gastronorm Refrigeration

Stylish design offering a choice of wide entry or standard gastronorm design combined with an easy to use control panel for excellent temperature control



**Garnet**



**Sapphire**

### Benefits

- Tough, durable stainless steel exterior and choice of interior finishes
- All cabinets accommodate 1/1 and 2/1 pans
- Easy to clean, hygienic stainless steel base with radius corners and removable shelf supports and racking
- Top mounted removable refrigeration system for easy service and maintenance
- Designed for 43°C ambient environments
- Self closing lockable doors with easy to clean handles
- Heavy duty swivel and brake castors for easy mobility
- CFC free and designed and built to international quality standards
- HACCP compliant



## Sapphire / Garnet

For over 20 years Williams Refrigeration has been a leader in refrigeration technology and design, marketing refrigeration products worldwide. Manufacturing a wide range of products to international quality and construction standards, Williams has gained a global reputation for strength, quality and reliability.

### Features

Designed and manufactured to the highest specification meeting international quality standards, the cabinets offer stylish design with easy to clean moulded handles.

### Construction

- Tough stainless steel exterior and interior (except rear) for durability
- Self closing lockable doors, opening to 90° and easy to change magnetic seal
- Swivel and brake castors for easy positioning
- 75mm CFC free insulation

### Refrigeration

Leading the way in refrigeration technology, all Williams products are CFC free and designed for efficient and cost effective operation.

- Top mounted removable, forced air refrigeration for easy servicing and maintenance
- Automatic defrost - off cycle above +1°C
- Waste heat recovery vaporiser
- Digital temperature controller
- Anti condensation heaters on cabinets operating below 0°C
- 240 volt 50 cycle single phase unit complete with fitted plug



## Control Panel

Stylish, state of the art control panel incorporates many features to ensure excellent temperature control and effective, easy to manage operation even in the busiest environment.

Easy to operate buttons and clear LED display allow you to be in control

- Adjustable operating temperature for maximum effectiveness even in the hottest environment
- Auto/manual defrost and defrost indicator
- Compressor running indicator

**The cabinets continue to function even if the Control Probe fails**

## Options

- Glass doors and half doors
- Pass through facility
- Adjustable legs instead of castors





**Garnet Specifications**

**G1T** Internal H1370mm x W587mm x D683mm



Model	Temp °C	Amp	Shelves	Net Cap Ltrs / Cu ft
<b>One Door</b>				
HG1T	+1 / +4	3.0	4	610/21
MG1T	-2 / +2	4.0	4	610/21
FG1T	-2 / +2	4.0	-	610/21
WG1T	+3 / +13	4.0	4	610/21
LG1T	-18 / -22	4.5	4	610/21
HLG1T	+1 / +4	6.0	2	290/10
	-18 / -22	4.5	2	290/10
CFG1T	0 / +3	4.0	4	610/10

**G2T** Internal H1370mm x W1249mm x D683mm



Model	Temp °C	Amp	Shelves	Net Cap Ltrs / Cu ft
<b>Two Door</b>				
HG2T	+1 / +4	4.0	8	1271/45
MG2T	-2 / +2	5.0	8	1271/45
WG2T	-3 / +13	5.0	8	1271/45
LG2T	-18 / -22	6.0	8	1271/45
HLG2T	+1 / +4	7.0	4	595/21
	-18 / -22	6.0	4	595/21
CFG2T	0 / +3	5.0	8	1271/45

**G3T** Internal H1370mm x W1249mm x D683mm



Model	Temp °C	Amp	Shelves	Net Cap Ltrs / Cu ft
<b>Three Door</b>				
HG3T	+1 / +4	7.0	12	2000/71
MG3T	-2 / +2	7.0	12	2000/71
LG3T	-18 / -22	9.0	12	2000/71
CFG3T	0 / +3	7.0	12	2000/71

**Sapphire Specifications**

**S1T** Internal H1370mm x W715mm x D560mm



Model	Temp °C	Amp	Shelves	Net Cap Ltrs / Cu ft
<b>One Door</b>				
HS1	+1 / +4	3.0	4	595/21
MS1	-2 / +2	4.0	4	595/21
LS1	-18 / -22	4.5	4	595/21
CFS1	0 / +3	3.0	4	595/21

**S2T** Internal H1370mm x W1505mm x D560mm



Model	Temp °C	Amp	Shelves	Net Cap Ltrs / Cu ft
<b>Two Door</b>				
HS2	+1 / +4	4.0	8	1273/45
MS2	-2 / +2	3.5	8	1273/45
LS2	-18 / -22	6.0	8	1273/45
CFS2	0 / +3	3.5	8	1273/45

*Installation of all cabinets require adequate ventilation  
We reserve the right to change the specifications without notice*



**Williams Refrigeration Australia Pty Ltd**

38-42 Gaine Rd Dandenong South Victoria 3175  
Telephone: 03 9799 4900 Facsimile: 03 9799 4911 FreeCall: 1800 338 148  
Email: wra@access.net.au www.williamsref.com.au ABN 25 006 630 084

